


Troughing-Slider Conveyor Models



The E-ZLIFT Troughing-Slider model is a medium duty conveyor designed to move loose and packaged materials at inclines up to 30 degrees. The conveyor's unique combination slider-roller bed makes it E-ZLIFT's most versatile belt conveyor.

Typical Uses Include:

Dirt, gravel, sand, aggregates, grain, powders, cement, coal, and sludges. Cartons, shingles, firewood, rolls, and more!



Direct drive unit

Features Include:


- Heavy duty 2-ply rubber covered belt with 2" high cleats on 48" centers
- Combination slider/roller bed
- 7/8" O.D. high strength steel tubing for 12' & 16' models, 1-1/4" O.D. on 21' through 36' models
- 15" Frame height
- Approximate 140 FPM belt speed
- Conveyor belt take-up adjustments
- Self-cleaning drive and idler belt pulleys
- Drive mounted at side of discharge end
- Electric motor or gas engine
- Start/Stop switch for electric motor
- For electric motor - direct drive speed reducer
- For gas engine - internal V-belt, roller chain reduction, and safety guards
- Fork pockets
- Operating, maintenance, and safety instructions

Accessories:

- Hopper
- Dolly and hitch assembly
- Tail-light assembly
- Towable elevating carriage

Options:

- Smooth belt
- Belt wiper
- Corrosion resistant PVC idler rollers
- Mini-cleated belt
- Forward/Stop/Reverse switch for electric motor



Belt slider rails and rollers

Detachable dolly with spring-tensioned locking handles



Tail-light assembly

Belt - 14" wide		
Model	Length	Approx. Wt.*
68-14	12 ft.	350 lbs.
70-14	16 ft.	400 lbs.
71-14	21 ft.	470 lbs.
73-14	26 ft.	520 lbs.
75-14	31 ft.	565 lbs.
77-14	36 ft.	635 lbs.
CAPACITIES - at 30° incline		
Lbs./Cu. Ft.	Tons/Hr.	
30	22	
50	36	
75	54	

Belt - 18" wide		
Model	Length	Approx. Wt.*
68-18	12 ft.	365 lbs.
70-18	16 ft.	420 lbs.
71-18	21 ft.	495 lbs.
73-18	26 ft.	550 lbs.
75-18	31 ft.	610 lbs.
77-18	36 ft.	690 lbs.
CAPACITIES - at 30° incline		
Lbs./Cu. Ft.	Tons/Hr.	
30	27	
50	45	
75	67	

Belt - 24" wide		
Model	Length	Approx. Wt.*
68-24	12 ft.	373 lbs.
70-24	16 ft.	443 lbs.
71-24	21 ft.	533 lbs.
73-24	26 ft.	595 lbs.
75-24	31 ft.	685 lbs.
77-24	36 ft.	790 lbs.
CAPACITIES - at 30° incline		
Lbs./Cu. Ft.	Tons/Hr.	
30	36	
50	60	
75	90	

Specifications subject to change without notice
*Weight w/o accessories

Multilift, Inc.

12410 W Cedar Dr, Lakewood, Colorado 80228
Denver Area: 303.733.5533 Fax: 303.733.5642
North American Toll Free: 1.800.821.9966

Email: ez@ezliftconveyors.com
Website: www.ezliftconveyors.com